DELTALIGHT®

ENTERO RD-M SOFT 93018 B

28411 9010 B

AVAILABLE IN
BLACK 28411 9010 B
GOLD COLOURED 28411 9010 GC
WHITE 28411 9010 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 92
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.DIMMABLE LED POWER SUPPLY 450mA-DC Optional REFLECTORS 30° & 45° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,1W / CRI>90 (R9: 50) / 3000K-1800K / 1618lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1618lm // 16,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	1190lm // 19W // 64lm/W

Requirements

LED POWER SUPPLY 450mA-DC DIM

Options

ENTERO RD-M MOUNTING SET S2

DELTALIGHT®

ENTERO RD-M SOFT 93018 B

28411 9010 B

Accessories

ENTERO M HONEYCOMB
ENTERO M LINEAR SPREAD LENS
ENTERO M SPREAD LENS
ENTERO M SOFTENING LENS
ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: **28411_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
System ceiling	-	
Plasterboard	-	
Stucanet	-	
Wood	-	
Concrete	ENTERO RD-M MOUNTING SET S2	Required
Concrete + plaster	ENTERO RD-M MOUNTING SET S2	Required
Lintel + plaster	ENTERO RD-M MOUNTING SET S2	Required
Hollow-core slab	ENTERO RD-M MOUNTING SET S2	Required
Hollow-core slab + plaster	ENTERO RD-M MOUNTING SET S2	Required
Stretched ceiling	-	

DELTALIGHT®

ENTERO RD-M SOFT 93018 B

28411 9010 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐

LED power supplies



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 1(0) ☐



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 1(0) ☐



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 1(0) ☐



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 1 ☐



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 1 ☐

DELTALIGHT®

ENTERO RD-M SOFT 93018 B

28411 9010 B

Light altering devices



28500 0070 ENTERO M LINEAR SPREAD LENS



28500 0080 ENTERO M SPREAD LENS



28500 0090 ENTERO M SOFTENING LENS



28500 0100 ENTERO M GLASS SBL



28500 0110 B ENTERO M HONEYCOMB SINGLE USE B



28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B

DELTALIGHT®

ENTERO RD-M SOFT 93018 B

28411 9010 B

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18° ☐



24611 0230 SPY 66 REFLECTOR 30° ☐



24611 0240 SPY 66 REFLECTOR 45° ☐

Mounting set S2



28500 0200 ENTERO RD-M MOUNTING SET S2 ☐

Notes: