





GIBBO 927 DIM8 B

286 67 811 920 ED8 B

AVAILABLE IN

BLACK 286 67 811 920 ED8 B

WHITE 286 67 811 920 ED8 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.GLASS INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTOMATIC 1.6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	738lm // 7W // 111lm/W

Requirements

BOWL GLASS CLEAR
BOWL GLASS AMBER
BOWL GLASS OPAL WHITE


GIBBO 927 DIM8 B

286 67 811 920 ED8 B

For detailed installation instructions, please consult the manual: [286_67_811_XXX_ED8_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Control gear, ballast and transformers




300 90 004 ED8 WIRELESS CONTROL DIM8

☐


To be used with ...



286 67 01 BOWL GLASS CLEAR

☐

286 67 02 BOWL GLASS AMBER

☐

286 67 03 BOWL GLASS OPAL WHITE

☐

Notes: