DELTALIGHT



M - CUPPA C 93040 MDL

REFERENCE 28811 9330 W-GC

AVAILABLE IN
BLACK-GOLD COLORED 28811 9330 B-GC
WHITE-GOLD COLORED 28811 9330 W-GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC INCL.1 x CABLE 2 x 0.75mm² / 1,6m

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	834lm // 10W // 84lm/W

Remarks

Black cable for B-GC version and grey cable for W-GC version

Requirements

CUPPA SHADE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

DELTALIGHT

M - CUPPA C 93040 MDL

28811 9330 W-GC

For detailed installation instructions, please consult the manual : **28811_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 19

Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 19

Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable

M - CUPPA C 93040 MDL

28811 9330 W-GC



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Suspension parts



15229 0010 B CABLE CLAMP B

Finish your product



28800 0010 B CUPPA SHADE 120 B

28800 0010 GC CUPPA SHADE 120 GC

28800 0010 W CUPPA SHADE 120 W



28800 0020 B CUPPA SHADE 190 B

28800 0020 GC CUPPA SHADE 190 GC

28800 0020 W CUPPA SHADE 190 W

M - CUPPA C 93040 MDL

28811 9330 W-GC



28800 0030 B CUPPA SHADE 300 B

28800 0030 GC CUPPA SHADE 300 GC

28800 0030 W CUPPA SHADE 300 W



28800 0040 B CUPPA DISK B

28800 0040 W CUPPA DISK W

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile	Available Colours
 **23359 0000** SLM26H - PROFILE	
 **23359 0010** SLM26H - PROFILE 1m	
 **23359 0020** SLM26H - PROFILE 2m	
 **23359 0030** SLM26H - PROFILE 3m	

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 **23358 0000** SLM26L - PROFILE	

M - CUPPA C 93040 MDL

28811 9330 W-GC



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m

SHIFTLINE M35R profile

Available Colours



23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m

SHIFTLINE M44 profile

Available Colours



23374 0000 SLM44 - PROFILE



23374 0020 SLM44 - PROFILE 2m

M - CUPPA C 93040 MDL

28811 9330 W-GC



23374 0030 SLM44 - PROFILE 3m

SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m



23397 0030 SPM20 ST - PROFILE 3m

SPLITLINE M20 profile

Available Colours



420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B

SPLITLINE M52 profile

Available Colours



420 52 10 00 SPM52 - PROFILE 1m

DELTALIGHT

M - CUPPA C 93040 MDL

28811 9330 W-GC



420 52 20 00 SPM52 - PROFILE 2m



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE

Notes: