





M26L - JUM-OH! 4R 92730 MDL

29413 9220 B

AVAILABLE IN
BLACK 29413 9220 B



 [View on website](#)



General info

| | |
|---------------------------|--|
| LOCATION | indoor |
| INSTALLATION | Low voltage systems Low voltage system mounted |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0.2 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | 4 x REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC |

Electrical info

| | |
|---------------------|------------------------------------|
| ELECTRICAL | 48V-DC |
| CLASS | III |
| DIM TYPE | MDL = 1-10V or DALI or push button |
| ENERGY CLASS | F |
| CERTIFICATES | CB, ENEC |

Lightsource info

| | |
|------------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | 2 x (LED cluster 4W / CRI>90 (R9: 55) / 2700K / 439lm) |
| TM-30 VALUES | Rf: 91 / Rg: 100 |
| SDCM | SDCM3 |
| RISKGROUP | RG2 |
| LM80 | L80 > 150000 |
| BEAMANGLE | 30° |
| LED TECHNICS (LIGHT SOURCE) | 878lm // 8W // 110lm/W |
| LED TECHNICS (LUMINAIRE) | 726lm // 9,2W // 79lm/W |

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [29413_XXX0_HAND.pdf](#)

DELTALIGHT

M26L - JUM-OH! 4R 92730 MDL

29413 9220 B

FINISH YOUR SPECIFICATION


Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

20

Dimtype: WDL = wireless dimmable


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

20

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

20

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN


26

Dimtype: non-dimmable

DELTALIGHT

M26L - JUM-OH! 4R 92730 MDL

29413 9220 B




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

21


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile

Available Colours



23375 0000 SLM35R - PROFILE




23375 0010 SLM35R - PROFILE 1m




DELTALIGHT

M26L - JUM-OH! 4R 92730 MDL

29413 9220 B



23375 0020 SLM35R - PROFILE 2m



23375 0030 SLM35R - PROFILE 3m



Notes: