





## M26L - JUM-OH! 4R 92730 DIM5

29414 9225 B

AVAILABLE IN  
**BLACK** 29414 9225 B



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	4 x REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	2 x (LED cluster 4W / CRI>90 (R9: 55) / 2700K / 439lm)
<b>TM-30 VALUES</b>	Rf: 91 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 150000
<b>BEAMANGLE</b>	30°
<b>LED TECHNICS (LIGHT SOURCE)</b>	878lm // 8W // 110lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	726lm // 9,2W // 79lm/W

### Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [29414\\_XXX5\\_HAND.pdf](#)

# DELTALIGHT

## M26L - JUM-OH! 4R 92730 DIM5

29414 9225 B

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

26

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

21

Dimtype: non-dimmable

Cutout dimension (mm): 40

### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

#### Available Colours



**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m




**23358 0020** SLM26L - PROFILE 2m



# DELTALIGHT

## M26L - JUM-OH! 4R 92730 DIM5

29414 9225 B




**23358 0030** SLM26L - PROFILE 3m




### SHIFTLINE M35R profile


Available Colours




**23375 0000** SLM35R - PROFILE



**23375 0010** SLM35R - PROFILE 1m



**23375 0020** SLM35R - PROFILE 2m



**23375 0030** SLM35R - PROFILE 3m



Notes: