





M26L - JUM-OH! 4R 92730 DIM5 B

29414 9225 B

AVAILABLE IN
BLACK 29414 9225 B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 4W / CRI>90 (R9: 50) / 2700K / 439lm)
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	878lm // 8W // 110lm/W
LED TECHNICS (LUMINAIRE)	726lm // 9W // 79lm/W

Requirements





LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual: [29414_XXX5_HAND.pdf](#)

M26L - JUM-OH! 4R 92730 DIM5 B

29414 9225 B









FINISH YOUR SPECIFICATION

LED power supplies		#
	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	10 <input type="checkbox"/>
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	26 <input type="checkbox"/>
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	10 <input type="checkbox"/>
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	21 <input type="checkbox"/>

M26L - JUM-OH! 4R 92730 DIM5 B
 29414 9225 B

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
--	-------------------

 <div> <div>32</div> <div>23358 0000 SLM26L - PROFILE</div> </div>	
 <div> <div>32</div> <div>23358 0010 SLM26L - PROFILE 1m</div> </div>	
 <div> <div>32</div> <div>23358 0020 SLM26L - PROFILE 2m</div> </div>	
 <div> <div>32</div> <div>23358 0030 SLM26L - PROFILE 3m</div> </div>	

Notes: