



OONO WS 927 DIM8

29611 9208 GM

AVAILABLE IN

ALU GREY 29611 9208 A



BLACK 29611 9208 B

FLEMISH BRONZE OUTDOOR 29611 9208 FBRX

GOLD MARBLED 29611 9208 GM

ANTHRACITE 29611 9208 N

WHITE 29611 9208 W



 [View on website](#)



General info

| | |
|---------------------------------------------|--------------------------------------------------------------------------------------------|
| LOCATION | indoor-outdoor |
| INSTALLATION | Wall Surface mounted |
| INGRESS PROTECTION | IP54 |
| PROTECTION AGAINST MECHANICAL IMPACT | IK04 |
| WEIGHT (KG) | 1.1 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | INCL.DIMMABLE LED POWER SUPPLY 500mA-DC GM (Gold Marbled) version only for interior use |

Electrical info

| | |
|---------------------|-----------------------|
| ELECTRICAL | 220-240V / 50-60Hz |
| CLASS | I |
| POWER SUPPLY | YES |
| DIM TYPE | mains (phase cut-off) |
| ENERGY CLASS | E |

Lightsource info

| | |
|------------------------------------|---------------------------------------------------|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm |
| TM-30 VALUES | rf: 89 / Rg: 100 |
| SDCM | SDCM1 |
| RISKGROUP | RG1 |
| LM80 | L90B10 > 50000 |
| LED TECHNICS (LIGHT SOURCE) | 1041lm // 8,6W // 121lm/W |
| LED TECHNICS (LUMINAIRE) | 572lm // 9,9W // 58lm/W |

For detailed installation instructions, please consult the manual : [29611_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

OONO W S 927 DIM8

29611 9208 GM