



OONO W M 930 DIM8

29612 9308 GM

AVAILABLE IN

ALU GREY 29612 9308 A



BLACK 29612 9308 B

FLEMISH BRONZE OUTDOOR 29612 9308 FBRX

GOLD MARBLED 29612 9308 GM

ANTHRACITE 29612 9308 N

WHITE 29612 9308 W



 [View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	2.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 700mA-DC GM (Gold Marbled) version only for interior use

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 52) / 3000K / 1467lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1467lm // 12,4W // 118lm/W
LED TECHNICS (LUMINAIRE)	773lm // 14,3W // 54lm/W

For detailed installation instructions, please consult the manual : [29612_XXX8_HAND.pdf](#)

Notes:

DELTALIGHT

OONO W M 930 DIM8

29612 9308 GM