



OONO T 930

29624 9000 AM

AVAILABLE IN

ALUMINIUM MARBLED 29624 9000 AM

GOLD MARBLED 29624 9000 GM



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Table top Stand alone
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.POWER ADAPTER dimmable by touch

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	III
POWER SUPPLY	YES
DIM TYPE	Touch
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	144lm // 6,9W // 21lm/W

For detailed installation instructions, please consult the manual : [29624_XXX0_HAND.pdf](#)

Notes: