



## LOGIC 190 R REFL 93032

30225 9320 INOX

AVAILABLE IN  
INOX 30225 9320 INOX



 [View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - BOX
<b>RECESSED DEPTH (MM)</b>	190
<b>INGRESS PROTECTION</b>	IP67
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK10
<b>WEIGHT (KG)</b>	2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-32° INCL.LED POWER SUPPLY 400mA-DC INCL.1 x CABLE H05 RN-F 3 x 0.75mm <sup>2</sup> 0,5m INCL.IP68 CONNECTOR 3P ESG 10mm max.500kg

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 13W / CRI>90 (R9: 52) / 3000K / 1855lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	32°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1855lm // 13W // 143lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1431lm // 15W // 96lm/W

### Requirements

LOGIC 190 R BOX

### Options

LOGIC 190 ANTI VANDAL SCREWS 2 PCS

# DELTALIGHT

## LOGIC 190 R REFL 93032


30225 9320 INOX

For detailed installation instructions, please consult the manual : [30225\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Ground mounting boxes

---




**30210 0010** LOGIC 190 R BOX


Cutout dimension (mm): 300 x 230

#### Waterproof connection parts

---




**431 99 02** IP68 JUNCTION BOX 4P



**21034 0150** IP68 Y-CONNECTOR 5P

#### Other

---



**30210 0020** LOGIC 190 ANTI VANDAL SCREWS 2 PCS

Notes: