



LOGIC W L 930 W

304 32 01 93 W

AVAILABLE IN



ALU GREY 304 32 01 93 A

BLACK 304 32 01 93 B

FLEMISH BRONZE OUTDOOR 304 32 01 93 FBRX

ANTHRACITE (DARK GREY) 304 32 01 93 N

WHITE 304 32 01 93 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	110-135
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS SBL INCL.LED POWER SUPPLY 350mA-DC INCL.1 x PG11

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,4W / CRI>90 (R9: 50) / 3000K / 1388lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1388lm // 9,4W // 147lm/W
LED TECHNICS (LUMINAIRE)	127lm // 11W // 12lm/W

Requirements


CONCRETE BOX 191

CONCRETE PACK LOGIC W L

For detailed installation instructions, please consult the manual: [304_32_01_XX_V04_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Concrete boxes



270 11 191 CONCRETE BOX 191

☐

Concrete packs



304 32 96 CONCRETE PACK LOGIC W L

☐

Notes: