
DELTALIGHT




LOGIC W L 930

REFERENCE 304 32 01 93 W

AVAILABLE IN
ALU GREY 304 32 01 93 A
BLACK 304 32 01 93 B
FLEMISH BRONZE OUTDOOR 304 32 01 93 FBRX
ANTHRACITE 304 32 01 93 N
WHITE 304 32 01 93 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	110-135
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS SBL INCL.LED POWER SUPPLY 350mA-DC INCL.1 x PG11

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,4W / CRI>90 (R9: 50) / 3000K / 1388lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1388lm // 9,4W // 147lm/W
LED TECHNICS (LUMINAIRE)	127lm // 11W // 12lm/W

Requirements

CONCRETE BOX 191
CONCRETE PACK LOGIC W L

For detailed installation instructions, please consult the manual : **304_32_01_XX_V04_HAND.pdf**


DELTALIGHT

LOGIC W L 930

304 32 01 93 W

FINISH YOUR SPECIFICATION


Concrete boxes



270 11 191 CONCRETE BOX 191

Cutout dimension (mm): 315 x 80

Concrete packs



304 32 96 CONCRETE PACK LOGIC W L

Cutout dimension (mm): 315 x 80

Notes: