

# DELTALIGHT



## LOGIC W S 930

304 33 811 930 W

AVAILABLE IN



**ALU GREY** 304 33 811 930 A

**BLACK** 304 33 811 930 B

**FLEMISH BRONZE OUTDOOR** 304 33 811 930 FBRX

**ANTHRACITE** 304 33 811 930 N

**WHITE** 304 33 811 930 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor-outdoor
<b>INSTALLATION</b>	Wall Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	rectangle - BOX
<b>RECESSED DEPTH (MM)</b>	115-140
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK03
<b>WEIGHT (KG)</b>	0.7
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	INCL.PC SBL INCL.LED POWER SUPPLY 350mA-DC INCL.1 x PG11

### Electrical info

<b>ELECTRICAL</b>	110-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	D

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	787lm // 5,8W // 135lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	172lm // 6,7W // 26lm/W

### Requirements


CONCRETE BOX 192  
CONCRETE PACK LOGIC W S

For detailed installation instructions, please consult the manual : [304\\_33\\_811\\_XXX\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Concrete boxes

---




**270 11 192** CONCRETE BOX 192



Cutout dimension (mm): 135 x 125

#### Concrete packs

---



**304 33 96** CONCRETE PACK LOGIC W S



Cutout dimension (mm): 135 x 125

Notes: