



## LOGIC MINI W R

304 30 12 A

AVAILABLE IN



**ALU GREY** 304 30 12 A

**BLACK** 304 30 12 B

**FLEMISH BRONZE OUTDOOR** 304 30 12 FBRX

**ANTHRACITE** 304 30 12 N

**WHITE** 304 30 12 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor-outdoor
<b>INSTALLATION</b>	Wall Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 55
<b>RECESSED DEPTH (MM)</b>	50
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	min.12
<b>INGRESS PROTECTION</b>	IP54
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK03
<b>WEIGHT (KG)</b>	0.2
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	EXCL.LED POWER SUPPLY 24V-DC

### Electrical info

<b>ELECTRICAL</b>	24V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	G

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED 0,6W / 3000K / 40lm
<b>LED TECHNICS (LIGHT SOURCE)</b>	40lm // 0,6W // 67lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	4lm // 0,7W // 5lm/W

### Requirements

LED POWER SUPPLY 24V-DC

### Options

CONCRETE BOX 188

For detailed installation instructions, please consult the manual : [304\\_30\\_12\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 89 24 20** LED POWER SUPPLY 24V-DC / 20W

30

Dimtype: non-dimmable

Cutout dimension (mm): 60




**300 89 24 40** LED POWER SUPPLY 24V-DC / 40W

60

Dimtype: non-dimmable

Cutout dimension (mm): 55




**300 89 24 60** LED POWER SUPPLY 24V-DC / 60W

90

Dimtype: non-dimmable


Cutout dimension (mm): 55



**300 89 24 61** LED POWER SUPPLY 24V-DC / 60W DIN

90

Dimtype: non-dimmable




**300 89 24 80 ED1** LED POWER SUPPLY 24V-DC / 80W DIM1

120

Dimtype: 1-10V

Cutout dimension (mm): 75




**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W

225

Dimtype: non-dimmable

Cutout dimension (mm): 75



**21012 0160** LED POWER SUPPLY 24V-DC / 24W

36

Dimtype: non-dimmable

Cutout dimension (mm): 55


# DELTALIGHT

## LOGIC MINI W R

304 30 12 A

### Concrete boxes

---



**270 11 188** CONCRETE BOX 188



**Cutout dimension (mm): 67**

Notes: