



OBIN ON 92736 DIM5 B

30511 9235 B

AVAILABLE IN

BLACK 30511 9235 B



BRUSHED ALU 30511 9235 BRA

BRUSHED ANTHRACITE 30511 9235 BRAT

BRUSHED GOLD 30511 9235 BRG

BRUSHED OLD BRONZE 30511 9235 BROB

WHITE 30511 9235 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-36° INCL.DIMMABLE POWER SUPPLY

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1458lm // 11,6W // 125lm/W
LED TECHNICS (LUMINAIRE)	1258lm // 13W // 94lm/W

Requirements

SPY 90 TUBE

Accessories

HONEYCOMB 75

OBIN ON 92736 DIM5 B

30511 9235 B

For detailed installation instructions, please consult the manual: [30511_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



19810 0110 B HONEYCOMB 75 SINGLE USE B

☐

Finish your product

 <p>19810 0170 B SPY 90 TUBE B</p>	<input type="checkbox"/>
<p>19810 0170 DC SPY 90 TUBE DC</p>	<input type="checkbox"/>
<p>19810 0170 FBR SPY 90 TUBE FBR</p>	<input type="checkbox"/>
<p>19810 0170 FG SPY 90 TUBE FG</p>	<input type="checkbox"/>
<p>19810 0170 GC SPY 90 TUBE GC</p>	<input type="checkbox"/>
<p>19810 0170 W SPY 90 TUBE W</p>	<input type="checkbox"/>

Notes: