





OBIN ON 92736 DIM5 B
30511 9235 B

AVAILABLE IN
BLACK 30511 9235 B
BRUSHED ALU 30511 9235 BRA
BRUSHED ANTHRACITE 30511 9235 BRAT
BRUSHED GOLD 30511 9235 BRG
BRUSHED OLD BRONZE 30511 9235 BROB
WHITE 30511 9235 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-36° INCL.DIMMABLE POWER SUPPLY

Electrical info	
ELECTRICAL	120-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1458lm // 11,6W // 125lm/W
LED TECHNICS (LUMINAIRE)	1258lm // 13W // 94lm/W

Requirements	
SPY 90 TUBE	

Accessories	
HONEYCOMB 75	

For detailed installation instructions, please consult the manual: [30511_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



13

19810 0110 B HONEYCOMB 75 SINGLE USE B

☐

Finish your product

 <div><div>28</div><div>19810 0170 B SPY 90 TUBE B</div></div>	<input type="checkbox"/>
<div><div>19810 0170 DC SPY 90 TUBE DC</div></div>	<input type="checkbox"/>
<div><div>19810 0170 FBR SPY 90 TUBE FBR</div></div>	<input type="checkbox"/>
<div><div>19810 0170 FG SPY 90 TUBE FG</div></div>	<input type="checkbox"/>
<div><div>19810 0170 GC SPY 90 TUBE GC</div></div>	<input type="checkbox"/>
<div><div>19810 0170 W SPY 90 TUBE W</div></div>	<input type="checkbox"/>

Notes: