





SUPER-OH! XS PIVOT 25 DIM8 W

308 22 02 83 ED8 W

AVAILABLE IN
BLACK 308 22 02 83 ED8 B
WHITE 308 22 02 83 ED8 W



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	INCL.PC SBL
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 13,5W / CRI>80 / 3000K / 1470lm
LED TECHNICS (LIGHT SOURCE)	1470lm // 13,5W // 109lm/W
LED TECHNICS (LUMINAIRE)	691lm // 16W // 45lm/W

For detailed installation instructions, please consult the manual: [308 22 02 XX ED8_HAND.pdf](#)

SUPER-OH! XS PIVOT 25 DIM8 W

308 22 02 83 ED8 W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment #



36,3 40,4 14

300 90 004 ED8 WIRELESS CONTROL DIM8

☐



153 36 54

300 90 126 FALLING EDGE DIMMER 200W DIM2

16 ☐

Notes: