





SUPER-OH! XS PIVOT 39 DIM8 W

308 22 03 83 ED8 W

AVAILABLE IN

BLACK 308 22 03 83 ED8 B

WHITE 308 22 03 83 ED8 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	INCL.PC SBL

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 25W / CRI>80 / 3000K / 2940lm
LED TECHNICS (LUMINAIRE)	1396lm // 29W // 49lm/W


For detailed installation instructions, please consult the manual: [308_22_03_XX_ED8_HAND.pdf](#)

SUPER-OH! XS PIVOT 39 DIM8 W


308 22 03 83 ED8 W

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers #



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

300 90 126 FALLING EDGE DIMMER 200W DIM2

8

☐

Notes: