





SUPER-OH! XS 39 C DIM8 B
308 241 03 83 ED8 B

AVAILABLE IN
BLACK 308 241 03 83 ED8 B
WHITE 308 241 03 83 ED8 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x PC SBL INCL.1 x CABLE 3 x 0,75mm ² 3m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 25W / CRI>80 / 3000K / 2940lm
LED TECHNICS (LIGHT SOURCE)	2940lm // 25W // 118lm/W
LED TECHNICS (LUMINAIRE)	1396lm // 29W // 49lm/W

Options

COVERSET R 90-100
SUPER-OH! XS CEILING BASE


For detailed installation instructions, please consult the manual: [308_241_03_83_ED8_HAND.pdf](#)

SUPER-OH! XS 39 C DIM8 B

308 241 03 83 ED8 B

FINISH YOUR SPECIFICATION


Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Coversets




204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Ceiling bases



308 24 99 B SUPER-OH! XS CEILING BASE B

☐

Notes:

 DELTALIGHT®

SUPER-OH! XS 39 C DIM8 B

308 241 03 83 ED8 B