



## M - LED LINE HE 1 x 12,6W MDL

421 313 06 93 MDL B

AVAILABLE IN

**BLACK** 421 313 06 93 MDL B



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	LED FLEX 21W/m 3000K / CRI90 2600lm/m EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, EAC, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED flex 12,6W / CRI>90 (R9: 60) / 3000K / 1500lm
<b>SDCM</b>	SDCM3
<b>LM80</b>	L70 > 30000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1500lm // 12,6W // 119lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	625lm // 14,5W // 43lm/W

### Remarks

**Take a look at our [MAGNETIC PROFILES movie](#)**

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [421\\_313\\_06\\_XX\\_MDL\\_HAND.pdf](#)

# DELTALIGHT

## M - LED LINE HE 1 x 12,6W MDL

421 313 06 93 MDL B

### FINISH YOUR SPECIFICATION


#### Current supply

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0030** SMART 48 MODULATOR PLUG-IN WD

13

Dimtype: WDL = wireless dimmable


#### SMART 48

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

13

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

13

Dimtype: WDL = wireless dimmable


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 89 48 90** LED POWER SUPPLY 48V-DC / 90W

6

Dimtype: non-dimmable

Cutout dimension (mm): 75



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN


7

Dimtype: non-dimmable

# DELTALIGHT

## M - LED LINE HE 1 x 12,6W MDL


421 313 06 93 MDL B



**300 89 48 150** LED POWER SUPPLY 48V-DC / 150W

10


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

16

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

7

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

13


Dimtype: non-dimmable

Cutout dimension (mm): 40


## COMPATIBLE COMPOSABLES

### SHIFTLINE M26 profile


### Available Colours



**420 26 10 00** SLM26 - PROFILE 1m



**420 26 20 00** SLM26 - PROFILE 2m




**420 26 30 00** SLM26 - PROFILE 3m



### SHIFTLINE M26H profile

### Available Colours




**23359 0000** SLM26H - PROFILE




# DELTALIGHT

## M - LED LINE HE 1 x 12,6W MDL


421 313 06 93 MDL B



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m




**23359 0030** SLM26H - PROFILE 3m




### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


#### Available Colours




**23358 0000** SLM26L - PROFILE




**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m




**23358 0030** SLM26L - PROFILE 3m




### SHIFTLINE M35R profile

#### Available Colours



**23375 0000** SLM35R - PROFILE




**23375 0010** SLM35R - PROFILE 1m




# DELTALIGHT

## M - LED LINE HE 1 x 12,6W MDL

421 313 06 93 MDL B



**23375 0020** SLM35R - PROFILE 2m




**23375 0030** SLM35R - PROFILE 3m




### SHIFTLINE M44 profile


#### Available Colours



**23374 0000** SLM44 - PROFILE



**23374 0020** SLM44 - PROFILE 2m



**23374 0030** SLM44 - PROFILE 3m



### SPLITLINE M20 ST profile

#### Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m



### SPLITLINE M20 profile

#### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m




# DELTALIGHT

## M - LED LINE HE 1 x 12,6W MDL


421 313 06 93 MDL B



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: