





M - MICROSPY 39 C 92745 MDL W

421 612 811 921 MDL W

AVAILABLE IN

BLACK 421 612 811 921 MDL B

WHITE 421 612 811 921 MDL W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	EAC, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 7W // 76lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR



M - MICROSPY 39 C 92745 MDL W

421 612 811 921 MDL W

For detailed installation instructions, please consult the manual: [421_612_811_XXX_MDL_HAND.pdf](#)

M - MICROSPY 39 C 92745 MDL W

421 612 811 921 MDL W

FINISH YOUR SPECIFICATION

Current supply #



21032 0030 SMART 48 MODULATOR PLUG-IN WD

23 ☐

SMART 48 #



300 90 011 SMART 48 MODULATOR DIM9


23 ☐



300 90 012 SMART 48 MODULATOR WD


23 ☐

LED power supplies #



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

12 ☐



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

29 ☐



21012 0230 LED POWER SUPPLY 48V-DC / 100W

12 ☐



































21012 0240 LED POWER SUPPLY 48V-DC / 200W

24 ☐

M - MICROSPY 39 C 92745 MDL W

421 612 811 921 MDL W

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	 
	23359 0010 SLM26H - PROFILE 1m	 
	23359 0020 SLM26H - PROFILE 2m	   
	23359 0030 SLM26H - PROFILE 3m	   
SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	   
	23358 0030 SLM26L - PROFILE 3m	   

M - MICROSPY 39 C 92745 MDL W

421 612 811 921 MDL W

SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m











23301 0000 SPM20 - PROFILE B



M - MICROSPY 39 C 92745 MDL W

421 612 811 921 MDL W

SPLITLINE M52 profile	Available Colours
<div>  </div> <div> 420 52 10 00 SPM52 - PROFILE 1m </div>	
<div>  </div> <div> 420 52 20 00 SPM52 - PROFILE 2m </div>	
<div>  </div> <div> 420 52 30 00 SPM52 - PROFILE 3m </div>	
<div>  </div> <div> 24413 0000 SPM52 - PROFILE </div>	

Notes: