





M - DOT.COM M4 92732 MDL B-B
424 612 04 922 MDL B-B

AVAILABLE IN
BLACK-BLACK 424 612 04 922 MDL B-B
BLACK-CHROMED 424 612 04 922 MDL B-C
BLACK-GOLD MATT 424 612 04 922 MDL B-MMAT



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR FL-32° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5,7W / CRI>90 (R9: 50) / 2700K / 631lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	631lm // 5,7W // 111lm/W
LED TECHNICS (LUMINAIRE)	462lm // 7W // 70lm/W

Remarks
Take a look at our MAGNETIC PROFILES movie

Requirements
LED POWER SUPPLY 48V-DC

Options
DIMMABLE MODULATOR



M - DOT.COM M4 92732 MDL B-B


424 612 04 922 MDL B-B

For detailed installation instructions, please consult the manual: [424_612_04_XX_MDL_HAND.pdf](#)

M - DOT.COM M4 92732 MDL B-B
 424 612 04 922 MDL B-B

FINISH YOUR SPECIFICATION

Current supply
 #



21032 0030 SMART 48 MODULATOR PLUG-IN WD

29

☐

SMART 48
 #



300 90 011 SMART 48 MODULATOR DIM9

29

☐



300 90 012 SMART 48 MODULATOR WD

29

☐


LED power supplies
 #



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

15

☐



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

37

☐



21012 0230 LED POWER SUPPLY 48V-DC / 100W

15

☐



21012 0240 LED POWER SUPPLY 48V-DC / 200W

31


☐

M - DOT.COM M4 92732 MDL B-B


424 612 04 922 MDL B-B

COMPATIBLE COMPOSABLES


SHIFTLINE M26H profile Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m




23359 0020 SLM26H - PROFILE 2m




23359 0030 SLM26H - PROFILE 3m




SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX) Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




















23358 0030 SLM26L - PROFILE 3m



M - DOT.COM M4 92732 MDL B-B

424 612 04 922 MDL B-B

SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	 
	23397 0020 SPM20 ST - PROFILE 2m	 
	23397 0030 SPM20 ST - PROFILE 3m	 

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: