





M - DOT.COM M4 93032 MDL B-B
424 612 04 932 MDL B-B

AVAILABLE IN
BLACK-BLACK 424 612 04 932 MDL B-B
BLACK-CHROMED 424 612 04 932 MDL B-C
BLACK-GOLD MATT 424 612 04 932 MDL B-MMAT



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	4 x REFLECTOR FL-32° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 5,7W / CRI>90 (R9: 50) / 3000K / 648lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	648lm // 5,7W // 114lm/W
LED TECHNICS (LUMINAIRE)	474lm // 7W // 72lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR



M - DOT.COM M4 93032 MDL B-B

424 612 04 932 MDL B-B

For detailed installation instructions, please consult the manual: [424_612_04_XX_MDL_HAND.pdf](#)

M - DOT.COM M4 93032 MDL B-B

424 612 04 932 MDL B-B

FINISH YOUR SPECIFICATION

Current supply #



21032 0030 SMART 48 MODULATOR PLUG-IN WD

29 ☐

SMART 48 #



300 90 011 SMART 48 MODULATOR DIM9

29 ☐



300 90 012 SMART 48 MODULATOR WD


29 ☐

LED power supplies #



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

15 ☐



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

37 ☐



21012 0230 LED POWER SUPPLY 48V-DC / 100W

15 ☐



































21012 0240 LED POWER SUPPLY 48V-DC / 200W

31 ☐

M - DOT.COM M4 93032 MDL B-B










424 612 04 932 MDL B-B









COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	 
	23359 0010 SLM26H - PROFILE 1m	 
	23359 0020 SLM26H - PROFILE 2m	   
	23359 0030 SLM26H - PROFILE 3m	   
SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	   
	23358 0030 SLM26L - PROFILE 3m	   

M - DOT.COM M4 93032 MDL B-B

424 612 04 932 MDL B-B

SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	 
	23397 0020 SPM20 ST - PROFILE 2m	 
	23397 0030 SPM20 ST - PROFILE 3m	 

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: