DELTALIGHT

PUNK 451 C 92740 DIM8

REFERENCE 471 221 922 ED8 BP

AVAILABLE IN
BLACK 471 221 922 ED8 B
BLACK PURE 471 221 922 ED8 BP
GOLD COLOURED 471 221 922 ED8 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 2700K / 587lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	587lm // 6,4W // 92lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7,4W // 66lm/W

Requirements

MIDISPY TUBE

Options

SUSPENSION + CONNECTION TRIMLESS
COVERSET R 90-100

For detailed installation instructions, please consult the manual : **471_221_XXX_ED8_HAND.pdf**

DELTALIGHT

PUNK 451 C 92740 DIM8

471 221 922 ED8 BP

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Coversets



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B

204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

DELTALIGHT

PUNK 451 C 92740 DIM8

471 221 922 ED8 BP

Finish your product

	**414 03 00 B**	MIDISPY TUBE B	☐
	414 03 00 FBR	MIDISPY TUBE FBR	☐
	414 03 00 FG	MIDISPY TUBE FG	☐
	414 03 00 MMAT	MIDISPY TUBE MMAT	☐
	414 03 00 SG	MIDISPY TUBE SG	☐
	414 03 00 W	MIDISPY TUBE W	☐

Notes: