





VIZIR ON 2 92733 DIM1 BBR-B

473 131 812 922 ED1 BBR-B

AVAILABLE IN  
**BLACK BRONZE-BLACK** 473 131 812 922 ED1 BBR-B  
**GOLD COLORED-BLACK** 473 131 812 922 ED1 GC-B  
**WHITE-WHITE** 473 131 812 922 ED1 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	756lm // 13W // 57lm/W

Requirements	
VIZIR TUBE	

Accessories	
VIZIR HONEYCOMB	
VIZIR SOFTENING LENS	


VIZIR ON 2 92733 DIM1 BBR-B

473 131 812 922 ED1 BBR-B

For detailed installation instructions, please consult the manual: [473\\_131\\_812\\_XXX\\_ED1\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Control gear, ballast and transformers




**300 90 016 ED1** WIRELESS CONTROL 5A DIM1

☐

Light altering devices




**473 03 01 B** VIZIR HONEYCOMB B

☐

**473 03 04** VIZIR SOFTENING LENS

☐

Finish your product



**473 01 00 B** VIZIR TUBE B

☐

**473 01 00 FBR** VIZIR TUBE FBR

☐

**473 01 00 FG** VIZIR TUBE FG

☐

**473 01 00 W** VIZIR TUBE W

☐



## VIZIR ON 2 92733 DIM1 BBR-B

473 131 812 922 ED1 BBR-B

Notes: