





BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

AVAILABLE IN
BLACK-BLACK 10726 9228 B-B
BLACK-FLEMISH BRONZE 10726 9228 B-FBR
BLACK-FLEMISH GOLD 10726 9228 B-FG
BLACK-GOLD MATT 10726 9228 B-MMAT
WHITE-WHITE 10726 9228 W-W



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	601lm // 7W // 90lm/W

Accessories	
BOXY HONEYCOMB	
BOXY SOFTENING LENS	
BOXY GLASS SBL	

BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

For detailed installation instructions, please consult the manual: [10726_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Control gear, ballast and transformers



36,3 40,4 14

300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Light altering devices



Ø40

251 70 03 01 B BOXY HONEYCOMB B


☐



Ø45 1,5

251 70 03 01 W BOXY HONEYCOMB W

☐



Ø40

251 70 03 04 B BOXY SOFTENING LENS B


☐



Ø45 1,5

251 70 03 04 W BOXY SOFTENING LENS W


☐



Ø40

251 70 03 05 B BOXY GLASS SBL B

☐



Ø45 1,5

251 70 03 05 W BOXY GLASS SBL W

☐



BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

Notes: