



BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

AVAILABLE IN



BLACK-BLACK 10726 9228 B-B

BLACK-FLEMISH BRONZE 10726 9228 B-FBR

BLACK-FLEMISH GOLD 10726 9228 B-FG

BLACK-GOLD MATT 10726 9228 B-MMAT

WHITE-WHITE 10726 9228 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	601lm // 7W // 90lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

For detailed installation instructions, please consult the manual: [10726_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



36,3 40,4 14

300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Light altering devices



Ø40



1.5 Ø45

251 70 03 01 B BOXY HONEYCOMB B

☐

251 70 03 01 W BOXY HONEYCOMB W

☐



Ø40



1.5 Ø45

251 70 03 04 B BOXY SOFTENING LENS B

☐

251 70 03 04 W BOXY SOFTENING LENS W

☐



Ø40



1.5 Ø45

251 70 03 05 B BOXY GLASS SBL B

☐

251 70 03 05 W BOXY GLASS SBL W

☐



BOXY L 92733 DIM8 B-FG

10726 9228 B-FG

Notes: