DELTALIGHT®

LOGIC 60 R 93020 ANO

213 45 811 932 ANO

AVAILABLE IN
ALU ANODIZED 213 45 811 932 ANO





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 61
RECESSED DEPTH (MM)	100
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.1 x CABLE H05 RN-F 2 x 1mm² 0,5m EXCL.LED POWER SUPPLY 350mA-DC IEC 60598-2-13 : max.150kg 25N/cm² ESG 5mm

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	727lm // 7W // 109lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT®

LOGIC 60 R 93020 ANO

213 45 811 932 ANO

Options

LOGIC 60 BOX R
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: **213_45_811_XXX_HAND.pdf**

DELTALIGHT®

LOGIC 60 R 93020 ANO

213 45 811 932 ANO

FINISH YOUR SPECIFICATION

LED power supplies			#
	**300 90 63**	LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) ☐
	**300 90 68**	LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) ☐
	**300 90 69**	LED POWER SUPPLY MULTI-POWER HV DIM9	2->5(5) ☐
	**300 90 124**	LED POWER SUPPLY MULTI-POWER DIM7	2 (2) ☐
	**300 90 125**	LED POWER SUPPLY MULTI-POWER MINI DIM5	2 (2) ☐
	**21012 0010**	LED POWER SUPPLY MULTI POWER	1->2 ☐
	**21012 0021**	LED POWER SUPPLY MULTI POWER DIM1	1->2 ☐
	**21012 0035**	LED POWER SUPPLY MULTI POWER DIM5	1->2 ☐
	**21012 005W**	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 ☐

DELTALIGHT®

LOGIC 60 R 93020 ANO

213 45 811 932 ANO



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 — 1



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 2



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 1-2(2)



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 1

Ground mounting boxes



213 19 10 LOGIC 60 BOX R

DELTALIGHT®

LOGIC 60 R 93020 ANO

213 45 811 932 ANO

Waterproof connection parts	#
 **216 12 00** CBOX	
 **216 12 01** IP68 CONNECTION KIT	
216 12 02 IP68 CONNECTOR 3P	
 **216 14 35** CBOX 350 mA / 10W	1

Notes: