DELTALIGHT®

LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

AVAILABLE IN
ALU ANODIZED 213 45 10 811 932 ANO





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 61
RECESSED DEPTH (MM)	100
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.1 x CABLE H05 RN-F 2 x 1mm² 0,5m EXCL.LED POWER SUPPLY 350mA-DC IEC 60598-2-13 : max.150kg 25N/cm² ESG 5mm

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	353lm // 7W // 53lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT®

LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

Options

LOGIC 60 BOX R
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: **213_45_10_811_XXX_HAND.pdf**

DELTALIGHT®

LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

FINISH YOUR SPECIFICATION

LED power supplies			#
	**300 90 63**	LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) ☐
	**300 90 68**	LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) ☐
	**300 90 69**	LED POWER SUPPLY MULTI-POWER HV DIM9	2->5(5) ☐
	**300 90 124**	LED POWER SUPPLY MULTI-POWER DIM7	2 (2) ☐
	**300 90 125**	LED POWER SUPPLY MULTI-POWER MINI DIM5	2 (2) ☐
	**21012 0010**	LED POWER SUPPLY MULTI POWER	1->2 ☐
	**21012 0021**	LED POWER SUPPLY MULTI POWER DIM1	1->2 ☐
	**21012 0035**	LED POWER SUPPLY MULTI POWER DIM5	1->2 ☐
	**21012 005W**	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 ☐

DELTALIGHT®

LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

	**21012 0258**	LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1
	**21012 0298**	LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2
	**21012 0480**	LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2)
	**21032 0295**	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1

Ground mounting boxes

	**213 19 10**	LOGIC 60 BOX R	

DELTALIGHT®

LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

Waterproof connection parts	#
 **216 12 00** CBOX	
 **216 12 01** IP68 CONNECTION KIT	
216 12 02 IP68 CONNECTOR 3P	
 **216 14 35** CBOX 350 mA / 10W	1

Notes: