



LOGIC W S 930 B

304 33 811 930 B

AVAILABLE IN



ALU GREY 304 33 811 930 A

BLACK 304 33 811 930 B

FLEMISH BRONZE OUTDOOR 304 33 811 930 FBRX

ANTHRACITE (DARK GREY) 304 33 811 930 N

WHITE 304 33 811 930 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	115-140
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY 350mA-DC INCL.1 x PG11

Electrical info

ELECTRICAL	110-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	172lm // 7W // 26lm/W

Requirements


CONCRETE BOX 192

CONCRETE PACK LOGIC W S

For detailed installation instructions, please consult the manual: [304_33_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Concrete boxes



270 11 192 CONCRETE BOX 192

☐

Concrete packs



304 33 96 CONCRETE PACK LOGIC W S

☐

Notes: