



SPY 52 TRIMLESS SOFT 93045 B

19812 9030 B

AVAILABLE IN



BLACK 19812 9030 B

FLEMISH BRONZE 19812 9030 FBR

FLEMISH GOLD 19812 9030 FG

GOLD COLORED 19812 9030 GC

WHITE 19812 9030 W



[View on website](#)

General info

LOCATION	interior
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCLLED POWER SUPPLY 250mA-DC Optional REFLECTOR 20° available

Electrical info

CLASS	III
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 8,3W / CRI>90 (R9: 50) / 3000K-1800K / 934lm
TM-30 Values	Rf: 90 / Rg: 99
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	934lm // 8,3W // 113lm/W
LED Technics (luminaire)	598lm // 10W // 63lm/W

Requirements

SPY 52 TUBE
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.
MOUNTING KIT AIR 103
LED POWER SUPPLY 250mA-DC DIM

SPY 52 TRIMLESS SOFT 93045 B












19812 9030 B

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual: [19812_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Plasterboard	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Stucanet	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT SPY 39/52 TRIMLESS CSC	Required
	 MOUNTING KIT SPY 39/52 TRIMLESS WSC	Required

SPY 52 TRIMLESS SOFT 93045 B

19812 9030 B


FINISH YOUR SPECIFICATION

LED power supplies

#


300 90 64 LED POWER SUPPLY MULTI-POWER DIM7

1(1)

☐


300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1(1)

☐



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

1->3(3)

☐



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1(1)

☐



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1)

☐



21012 0095 LED POWER SUPPLY 250mA-DC / 10W DIM5

1

☐


21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

1

☐


21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1

☐

SPY 52 TRIMLESS SOFT 93045 B

19812 9030 B

Mounting kits



15212 2030 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

☐

Mounting kits stretched ceiling



15212 0080 MOUNTING KIT SPY 39/52 TRIMLESS CSC

☐



15212 0160 MOUNTING KIT SPY 39/52 TRIMLESS WSC







☐

 DELTALIGHT®

SPY 52 TRIMLESS SOFT 93045 B

19812 9030 B

Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	<input type="checkbox"/>
	19810 0020 LINEAR SPREAD LENS 42	<input type="checkbox"/>
	19810 0030 SPREAD LENS 42	<input type="checkbox"/>
	19810 0040 SOFTENING LENS 42	<input type="checkbox"/>
	19810 0050 GLASS SBL 42	<input type="checkbox"/>
	19810 0060 B HONEYCOMB 42 DOUBLE USE B	<input type="checkbox"/>

SPY 52 TRIMLESS SOFT 93045 B

19812 9030 B

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

19810 0100 FG SPY 52 TUBE FG

☐


19810 0100 GC SPY 52 TUBE GC

☐


19810 0100 W SPY 52 TUBE W

☐

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°

☐

Notes: