



SUPERNOVA LINE 65 930 DIM5

20622 9305 B

AVAILABLE IN

BLACK 20622 9305 B

WHITE 20622 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	6.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	8635lm // 58,8W // 147lm/W
LED TECHNICS (LUMINAIRE)	6165lm // 67,6W // 91lm/W

Options

- SUSPENSION SET 18 DIM1 3m
- CABLE BASE R / S + COVERSET R / S
- CENTRAL ROD SUSPENSION
- SUPERNOVA 65 RECESSED KIT
- WIRELESS CONTROL DIM5

For detailed installation instructions, please consult the manual : [20622_XXX5_HAND.pdf](#)

DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B

203 99 56 W CABLE BASE S W

Miscellaneous control equipment




300 90 004 ED5 WIRELESS CONTROL DIM5

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

Recessed kits



274 94 0710 SUPERNOVA 65 RECESSED KIT


 Cutout dimension (mm): 735

DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B


Coversets



204 00 62 ANO COVERSET R 62 ANO

204 00 62 B COVERSET R 62 B


204 00 62 W COVERSET R 62 W



204 00 90 ANO COVERSET R 90 ANO

204 00 90 B COVERSET R 90 B


204 00 90 W COVERSET R 90 W



204 00 100 ANO COVERSET R 100 ANO

204 00 100 B COVERSET R 100 B


204 00 100 W COVERSET R 100 W



204 62 62 ANO COVERSET S 62 ANO

204 62 62 B COVERSET S 62 B

204 62 62 W COVERSET S 62 W



204 80 80 ANO COVERSET S 80 ANO


204 80 80 B COVERSET S 80 B

DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

204 80 80 W COVERSET S 80 W



204 90 90 ANO COVERSET S 90 ANO


204 90 90 B COVERSET S 90 B

204 90 90 W COVERSET S 90 W

Suspension parts


328 18 43 ED1 SUSPENSION SET 18 DIM1 3m

Dimtype: 1-10V



328 24 61 B CENTRAL ROD SUSPENSION 65 1m B

328 24 61 W CENTRAL ROD SUSPENSION 65 1m W



328 24 91 B CENTRAL ROD SUSPENSION 95 1m B

328 24 91 W CENTRAL ROD SUSPENSION 95 1m W

Electric connection parts



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

DELTALIGHT

SUPERNOVA LINE 65 930 DIM5

20622 9305 B

Notes: