







SPY II 39 CABLE TRIMLESS CRI90 2700K 35° NO DIM

12304321ND00-9027W1-26332626-0000




 Image shows default finishes. Refer to the specifications below for the selected finishes per part.

Selected finishes per part





BODY

 White (26)



CABLE

 Woven Grey (33)



BASE

 White (26)



TUBE

 White (26)



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
CUTOUT SHAPE/SIZE (MM)	round - Ø kit
RECESSED DEPTH (MM)	50mm
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7

Electrical info

CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 974lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	35°
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	737lm // 9,9W // 74lm/W

Requirements

MOUNTING KIT CLIP TRIMLESS

DELTALIGHT











SPY II 39 CABLE TRIMLESS CRI90 2700K 35° NO DIM

12304321ND00-9027W1-26332626-0000

Accessories


SOFTENING LENS 39
SANDBLASTED LENS 39
LINEAR SPREAD LENS 39
HONEYCOMB 39

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 Plasterboard	 32210 0040 - MOUNTING KIT R37 TRIMLESS O.F.A.	<input type="checkbox"/> Required
 Concrete + plaster	 32210 0040 - MOUNTING KIT R37 TRIMLESS O.F.A.	<input type="checkbox"/> Required
 Lintel + plaster	 32210 0040 - MOUNTING KIT R37 TRIMLESS O.F.A.	<input type="checkbox"/> Required
 Hollow-core slab	 32210 0040 - MOUNTING KIT R37 TRIMLESS O.F.A.	<input type="checkbox"/> Required
 Hollow-core slab + plaster	 32210 0040 - MOUNTING KIT R37 TRIMLESS O.F.A.	<input type="checkbox"/> Required

ACCESSORIES

Mounting kits



32210 0040 MOUNTING KIT R37 TRIMLESS O.F.A

Cutout dimension (mm) : 72

Light altering devices



32210 0210 SOFTENING LENS 39



32210 0220 SANDBLASTED LENS 39



32210 0230 LINEAR SPREAD LENS 39

DELTALIGHT

SPY II 39 CABLE TRIMLESS CRI90 2700K 35° NO DIM

12304321ND00-9027W1-26332626-0000



32210 0240 HONEYCOMB 39



Notes: