DELTALIGHT



SUPERNOVA FLAT 65 930

REFERENCE 20631 9300 B

AVAILABLE IN
BLACK 20631 9300 B
WHITE 20631 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.ADJUSTABLE LED POWER SUPPLY - 2 settings: 1- 1400mA 2- 930mA

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 1400mA: LED cluster 58,5W / CRI>90 (R9: 68) / 3000K / 7776lm Or @ 930mA: LED cluster 37,4W / CRI>90 (R9: 68) / 3000K / 5360lm
TM-30 VALUES	Rf: 89 / Rg: 97 @ 930mA: Rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 1400mA: 7776lm // 58,5W // 132lm/W Or @ 930mA: 5360lm // 37,4W // 144lm/W
LED TECHNICS (LUMINAIRE)	@ 1400mA: 5928lm // 67W // 88lm/W Or @ 930mA: 4086lm // 43W // 95lm/W

Options

SUSPENSION SET 25 3m
CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

DELTALIGHT

SUPERNOVA FLAT 65 930

20631 9300 B

For detailed installation instructions, please consult the manual : **20631_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Coversets



204 00 62 ANO COVERSET R 62 ANO ☐

204 00 62 B COVERSET R 62 B ☐

204 00 62 W COVERSET R 62 W ☐



204 00 90 ANO COVERSET R 90 ANO ☐

DELTALIGHT

SUPERNOVA FLAT 65 930

20631 9300 B

	204 00 90 B	COVERSET R 90 B	☐
	204 00 90 W	COVERSET R 90 W	☐
	**204 00 100 ANO**	COVERSET R 100 ANO	☐
	204 00 100 B	COVERSET R 100 B	☐
	204 00 100 W	COVERSET R 100 W	☐
	**204 62 62 ANO**	COVERSET S 62 ANO	☐
	204 62 62 B	COVERSET S 62 B	☐
	204 62 62 W	COVERSET S 62 W	☐
	**204 80 80 ANO**	COVERSET S 80 ANO	☐
	204 80 80 B	COVERSET S 80 B	☐
	204 80 80 W	COVERSET S 80 W	☐
	**204 90 90 ANO**	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 65 930

20631 9300 B

Suspension parts



274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B ☐

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W ☐



328 25 43 SUSPENSION SET 25 3m ☐



328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B ☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W ☐

Electric connection parts



15225 0360 B CONNECTION ST B ☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W ☐

Notes: