DELTALIGHT



LOGIC LINEAR ON 880 92715 DIM5

REFERENCE 30835 9215 A

AVAILABLE IN
ALU GREY 30835 9215 A
BLACK 30835 9215 B
FLEMISH BRONZE OUTDOOR 30835 9215 FBRX
ANTHRACITE 30835 9215 N
WHITE 30835 9215 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2
INFORMATION	16 x LENS SP-15° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 55) / 2700K / 3288lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	3288lm // 28,8W // 111lm/W
LED TECHNICS (LUMINAIRE)	2880lm // 33W // 87lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING SET IP68

DELTALIGHT

LOGIC LINEAR ON 880 92715 DIM5

30835 9215 A

For detailed installation instructions, please consult the manual : **30835_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0390 LED POWER SUPPLY 48V-DC / 90W — 2

Dimtype: non-dimmable

Cutout dimension (mm): 75

Fixation components



30810 0040 LOGIC LINEAR 880 BOX EXTEND

30810 0040 INOX WALL BRACKET SET 60 INOX

30810 0040 N WALL BRACKET SET 60 N



30810 0050 INOX WALL BRACKET SET 100 INOX

30810 0050 N WALL BRACKET SET 100 N



30810 0060 INOX WALL BRACKET SET 200 INOX

30810 0060 N WALL BRACKET SET 200 N

DELTALIGHT

LOGIC LINEAR ON 880 92715 DIM5

30835 9215 A



30810 0070 INOX FLOOR BRACKET SET INOX

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m



30810 0090 IP68 CABLE + CONNECTOR 5P - 2m



30810 0110 THROUGH WIRING SET IP68 880

Notes: