
DELTALIGHT




SOLI - 52 92720 MDL

REFERENCE 27112 9220 B

AVAILABLE IN
BLACK 27112 9220 B
GOLD COLOURED 27112 9220 GC
WHITE 27112 9220 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,3W / CRI>90 (R9: 60) / 2700K / 1224lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1224lm // 10,3W // 119lm/W
LED TECHNICS (LUMINAIRE)	767lm // 12W // 65lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT

SOLI - 52 92720 MDL

27112 9220 B

For detailed installation instructions, please consult the manual : **27112_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 16


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 8

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 20

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 8


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SOLI - 52 92720 MDL

27112 9220 B




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 16


Dimtype: non-dimmable

Cutout dimension (mm): 40


Light altering devices




19810 0010 B HONEYCOMB 42 SINGLE USE B




19810 0020 LINEAR SPREAD LENS 42




19810 0030 SPREAD LENS 42



19810 0040 SOFTENING LENS 42




19810 0050 GLASS SBL 42



19810 0060 B HONEYCOMB 42 DOUBLE USE B

Finish your product



19810 0100 B SPY 52 TUBE B




19810 0100 FBR SPY 52 TUBE FBR

SOLI - 52 92720 MDL



27112 9220 B

19810 0100 FG	SPY 52 TUBE FG	☐
19810 0100 GC	SPY 52 TUBE GC	☐
19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	**19810 0180** SPY 52 REFLECTOR 20°	☐
	**19810 0190** SPY 52 REFLECTOR 45°	☐
	**19810 0240** SPY 52 REFLECTOR 30°	☐

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 **27111 0020** SOLI - PROFILE 2m	● ○
 **27111 0030** SOLI - PROFILE 3m	● ○

Notes: