DELTALIGHT

NOCTA SQ155 VWFL 927

REFERENCE 30123 9200 A

AVAILABLE IN
ALU GREY 30123 9200 A
BLACK 30123 9200 B
FLEMISH BRONZE OUTDOOR 30123 9200 FBRX
ANTHRACITE 30123 9200 N
WHITE 30123 9200 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LENS INCL.LED POWER SUPPLY 350 mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 702lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	702lm // 5,8W // 121lm/W
LED TECHNICS (LUMINAIRE)	428lm // 7W // 64lm/W

For detailed installation instructions, please consult the manual : **30123_XXX0_HAND.pdf**

DELTALIGHT

NOCTA SQ155 VWFL 927

30123 9200 A

Notes: